

# INSTALLATION INSTRUCTION FOR WEST MARINE MODEL 1193119 STEREO BOX SPEAKER WM-8000

1. WHEN MOUNTING SPEAKERS, USE THE MOUNTING BRACKET AS A TEMPLATE FOR MARKING AND DRILLING THREE HOLES.
2. ASSEMBLE MOUNTING SCREWS, SPRING WASHERS, FLAT WASHERS AND NUTS TO ATTACH MOUNTING BRACKETS TO MOUNTING SURFACE.
3. CONNECT INSULATED SPEAKER WIRE TO THE SPEAKER USING THE RED WIRE AS POSITIVE LEAD WHICH SHOULD BE CONNECTED TO THE POSITIVE TERMINAL AND THE BLACK WIRE AS NEGATIVE LEAD TO THE NEGATIVE TERMINAL. WE RECOMMEND FILLING ALL HOLES WHERE FASTENERS AND WIRES PIERCE DECKS AND BULKHEAD WITH SILICONE CAULKING TO PREVENT WATER LEAKAGE.
4. THE SCREWS, SPRING WASHERS AND MOUNTING BRACKET ARE PROVIDED TO MOUNT THE SPEAKER. RECOMMEND USING LOCK WASHERS OR LOCK NUTS TO PREVENT ACCIDENTAL LOOSENING ATTRIBUTABLE TO THE MANY VIBRATIONS ON BOATS.
5. ADJUST POSITION OF THE SPEAKER TO OBTAIN THE DESIRED MUSIC SOUND, THE MOUNTING PROCEDURE IS NOW COMPLETED.

6. PARTS INCLUDED:

- |                    |        |
|--------------------|--------|
| • INSULATED CORD   | 2 EACH |
| • MOUNTING BRACKET | 2 EACH |
| • BRACKET KNOB     | 4 EACH |
| • MOUNTING SCREW   | 4 EACH |
| • FLAT WASHER      | 4 EACH |
| • SPRING WASHER    | 4 EACH |
| • SCREW NUT        | 4 EACH |

