

AWLWOOD MA


EXTERIOR CLEARS SYSTEM

PRODUCT INFORMATION

WWW.AWLGRIP.COM

FEATURES & BENEFITS

- High building, fast curing formulation allowing multiple applications per day reducing work time
- Applicable over a wide range of temperatures and humidity by various methods so the same great result every time
- Remains highly flexible throughout lifetime of system which allows natural substrate movement whilst giving excellent toughness and abrasion resistance
- Use of the full system gives a synergistic effect resulting in extended performance retaining the same gloss, DOI and natural appearance as first application



Awlwood MA is an exterior clear system that is made up of a Primer and Clear Finish (available as satin or gloss). By combining the Primer and Clear together, the synergistic effect results in an outstanding performing system that adheres and bonds directly to the wood cellular structure giving extended performance and retaining the same gloss, DOI and natural appearance as first application.

SPECIFICATION DATA

Description	Sales Code	Part	VOC (Mixed and Unreduced)	Reducers
Primer	J3809	Clear Primer	500g/l or 4.17lb/gal	OT0201 (Brush) OT0202 (Spray)
	J7809	Red Tone Primer		
	J9809	Yellow Tone Primer		
Finish	J3890	Gloss	490g/l or 4.01lb/gal	

SYSTEM

(illustrative of products only)

FINISH

WFT: Vertical application: 2.6 mils (66 microns)
Horizontal application: 4.0 mils (100 microns)

Gloss: DFT: Vertical application: 1.3 mils (34 microns)
Horizontal application: 2.0 mils (50 microns)

PRIMER

WFT: ~4.0 mils (100 microns)* | DFT: 2.0 mils (50 microns)

ALL WOOD SUBSTRATES

Sand with no finer than 120 grit

* = Dependant upon timber absorbency, figure is given as a guide only



AkzoNobel

AWLWOOD MA

EXTERIOR CLEARS SYSTEM

PRODUCT INFORMATION

WWW.AWLGRIP.COM

AWLWOOD MA PRIMER

FEATURES & BENEFITS

- Formulated to deeply penetrate the grain/wood, even tropical hardwoods and thus give longer lasting colour stability and improved system adhesion
- Has a chemical affinity for the wood and locks directly onto the wood structure – gives superior flexibility and unrivalled resistance to delamination at damage points
- Penetrates deep into the wood grain allowing the natural colour and grain of wood to shine through
- Contains high performance colourants that impregnate the wood structure to mimic the tonings of the natural wood colourants – As natural colour of wood fades due to white light, colourants take over and retain their initial colour leaving the wood with a rich appearance

RECOMMENDED
COATS

1

AWLWOOD MA FINISH

FEATURES & BENEFITS

- Features an inherently non-yellowing polymer further stabilised with high performance UV absorbers giving long term clarity of film and excellent gloss and DOI retention
- Elastomeric nature of the cured film results in excellent toughness and abrasion resistance giving amazing in-service performance
- When combined with Awlwood MA Primers gives outstanding performance extending re-coat cycle times

RECOMMENDED
COATS

8

Visit us at www.awlgrip.com for further information.

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk and, to the extent permitted by law, we can accept no responsibility for the performance of the product or for any loss or damage arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Awlgrip[®], the AkzoNobel logo and all products mentioned in this publication are trademarks of, or licensed to, AkzoNobel. © Akzo Nobel N.V. 2012.



NORTH AMERICA 2270 Morris Avenue Union New Jersey 07083 TEL: 888.355.3090 FAX: 908.686.8545

EUROPE Bannerlaan 54 2280 Grobbendonk Belgium TEL: 32.14.25.7770 FAX: 32.14.23.0880

AUSTRALIA Unit E54 Gold Coast City Marina 76 Waterway Drive Coomera Queensland 4209 Australia
TEL: 61.7.5573.9655 or 1800.007.866 FAX: 61.7.5573.9677

NEW ZEALAND 686 Rosebank Road Avondale Auckland New Zealand TEL: 64.9.828.3009 or 0800.150.527 FAX: 64.9.828.1129

ASIA International Paint Singapore Pte Ltd 3 Neythal Road Singapore 628570 TEL: 65 6862 2928 FAX: 65 6862 0778