





Ahead of the Curve®

# It sounds even better.



▲ Display Theme 1, optimized for Day Mode



Display Theme 2, optimized for Night Mode ▲

## MediaMaster® 100s BE

The MediaMaster® 100s-BE is a premium, marine-grade source unit, designed for great audio performance on your boat, UTV and many other outdoor applications.

Multiple audio entertainment options are on-board, including Bluetooth® connectivity with AptX™ technology, a USB connection for a USB drive or iPhone®, an Analog AUX input, and a Digital AM/FM/Weather Band Tuner. MM100s-BE is also SiriusXM-Ready™ (tuner, antenna and subscription sold separately).

A rugged, weatherproof (IP66 rated) chassis houses a full-color LCD display, with separate Day/Night lighting themes for visibility, even in bright sunshine. When in motion, you will also appreciate the clean, uncluttered user interface with big text and large backlit controls.

The MM100s-BE has no on-board amplifier and will not drive speakers directly. Instead, it has eight channels of crystal-clear audio preamp outputs to feed outboard amplifiers, organized into four separate, nameable audio zones, each with its own flexible audio controls. A four-zone volume control system with on-the-fly level adjustment is very simple to use, and gives you fast access and complete control of volume levels in different areas of the boat.

The MM100s-BE is also NMEA 2000® Certified for connection with a variety of Marine Multifunction Displays (MFD's). Please visit our website and your MFD manufacturer's website for specific compatibility information.



### Built-in AM/FM/Weather Band Tuner with RDS

Digital AM/FM Tuner with NOAA weatherband capability. Radio Data System displays channel, category and program information for FM broadcasts, where available. A radio antenna is required (sold separately).



### SiriusXM-Ready™

Enjoy Commercial-free music, plus the best sports, exclusive talk and entertainment, comedy, news, traffic, weather and more when you add a SiriusXM® Connect Vehicle Tuner - sold separately.



### USB Input and Charging

USB 2.0 direct-digital connection for your compatible iPhone® or USB storage device.



### Auxiliary Input

A pair of analog audio inputs permit connection of any audio source with stereo analog outputs.



### Bluetooth® Audio Streaming

Allows a Bluetooth® equipped smartphone or portable media device to stream music to your audio system. Wirelessly control Play/Pause and Track Up/Down functions from your MediaMaster® 100s via Bluetooth®.



### Advanced AptX® Codec

Delivers maximum audio fidelity from compatible Bluetooth® streaming devices.



### NEW! - Certified NMEA 2000® Connectivity

Equipped with a NMEA 2000® connector (Micro-C), the MM100s-BE interfaces directly with existing vessel networks. Compatible MFD (Multi-Function Display) include models from Garmin, Lowrance and Simrad (Refer to MFD manufacturer for device compatibility info).

Electrical Specifications	
Operating Voltage	14.4V DC (10V – 15.9V allowable)
Maximum Current Draw	1.5 A
Standby Current Draw	120 mA
Fuse Value	5 A
Operating Temp Range	-4 F to +158 F (-20 C to +70 C)
Display	
Size / Type	3.5-inch / TFT LCD backlit
Resolution	320 x 240
Audio Outputs/Inputs	
Output Channels	4 stereo pairs of RCA plugs
Output Zones	Relative, Absolute, Fixed or Off
Maximum Output Voltage	4V RMS (Relative or Absolute) Selectable 4V/2V/1V RMS (Fixed)
Output Impedance	250 ohm
Input Channels	1 stereo pair of RCA plugs (2V/1V RMS input sensitivity)
Tuner	
FM Tuner with RDS	87.5 MHz to 107.9 MHz (0.2 MHz step)
AM Tuner	530 kHz to 1710 kHz (10 kHz step)
NOAA Weather Band Tuner	162.400 MHz to 162.550 MHz (0.025 MHz step)
Favorites	18 presets across all tuners
Bluetooth®	
Profile	A2DP v1.2, AVRCP v1.4
Core Specification	Version 2.1 + EDR
Codec	SBC, aptX®
Connection Range	Up to 35 ft / 11 m
USB	
Interface	USB 2.0 host
Maximum Current Output	1 A
Supported Audio Formats	MP3, WAV, WMA
Dimensions	
Unit W x H x D	5.94 in. x 3.90 in. x 3.17 in. (151 mm x 99 mm x 80.5 mm)
Mounting Hole W x H	4.70 in. x 3.25 in. (119.50 mm x 82.50 mm)

### MediaMaster® Accessories



MMR-20-BE Round Wired Remote 2.36-in. (360 mm)  
Wired, non-display remote for MM100s-BE



MMR-10W Wireless Remote  
Wireless key-fob style remote for MM100s-BE



MMC-6 Remote Cable  
6-foot cable for MMR-20 wired remote  
MMC-25 Remote Cable  
25-foot cable for MMR-20 wired remote  
MMC-2Y Remote Cable Y-Splitter  
Y-adaptor cable for MMC-6 and MMC-25 remote cables



©2017 JL Audio, Inc. "JL Audio", "Ahead of the Curve" and the JL Audio logo are registered trademarks of JL Audio, Inc. Sirius XM Radio Inc. Sirius, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The aptX® word mark and logos are registered trademarks owned by CSR. iPhone® and Lightning™ are registered trademarks of Apple Inc. Use of all trademarks by JL Audio is under license. Due to our policy of continuous product development, all specifications are subject to change without notice.

www.jlaudio.com  
10369 North Commerce Parkway • Miramar, Florida • 33025 • USA

05-2017  
Printed in U.S.A.