

Kinetik[®] Phantom LFP

ENERGY . POWER . STYLE



- Solid brass terminals
- 100% copper wire and soldered connections
- Internal battery balancing system
- Battery gauge to indicate state of charge
- Environmentally friendly; no harmful pollutants, corrosive acids, or toxic heavy metals
- Premium charge acceptance; rechargeable with faster and higher currents than Lead-Acid
- Polypropylene case
- Ultra-light weight; 1/3 of normal Lead-Acid battery weight
- Cycle life over 2000 cycles under JISD standard
- Shelf life exceeds 1 year
- Safe Lithium Iron Phosphate chemistry and soft pack process ensures high safety performance
- Higher starting voltage improves starting time
- Will not spill or leak as battery contains no acid
- For starting mass produced internal combustion engines only



www.kinetikpower.com



LITHIUM TECHNOLOGY

With
**Solid Brass
Terminals**



Case #1

Length: 4.21in (107mm) • Width: 2.2 in (56mm) • Height: 3.35 in(85)mm

Stock Code	Model No.	Polarity	Replaces	Replaces	UPC	Weight (lb)	Weight w/ box & foam (lb)	Weight (kg)	Weight w/ box & foam (kg)	Case Qty	LFP Actual Ah	Max Charge Current	CCA
48120	APP7L	+ -	48051	APP09A2-BS12	806593481208	1.1	1.4	0.5	0.64	8	2	10A	120
48121	APP7R	- +	48050 48052	APP07L2-BS12 APP09L2-BS12	806593481215	1.1	1.4	0.5	0.64	8	2	10A	120

Case #2

Length: 5.28 in (134mm) • Width: 2.56 in (65mm) • Height: 3.62 in(92)mm

Stock Code	Model No.	Polarity	Replaces	Replaces	UPC	Weight (lb)	Weight w/ box & foam (lb)	Weight (kg)	Weight w/ box & foam (kg)	Case Qty	LFP Actual Ah	Max Charge Current	CCA
48122	APP12L	+ -	48053	APP12A1-BS12	806593481222	1.7	2.0	0.77	0.91	6	3	10A	180
48123	APP14L	+ -	48057 48056 48055	APP14A5-BS12 APP14A4-BS12 APP14A2-BS12	806593481239	2.0	2.5	0.91	1.13	6	4	10A	240
48124	APP14R	- +	48059 48058	APP14L5-BS12 APP14L2-BS12	806593481246	2.0	2.5	0.91	1.13	6	4	10A	240

Case #3

Length: 5.83 (148mm) • Width: 3.4 in (86mm) • Height: 4.13 in(105)mm

Stock Code	Model No.	Polarity	Replaces	Replaces	UPC	Weight (lb)	Weight w/ box & foam (lb)	Weight (kg)	Weight w/ box & foam (kg)	Case Qty	LFP Actual Ah	Max Charge Current	CCA
48125	APP16L	+ -	48060	APP18A1-BS12	806593481253	3.0	3.5	1.36	1.6	6	6	24A	330
48126	APP16R	- +	48062	APP18L1-BS12	806593481260	3.0	3.5	1.36	1.6	6	6	24A	330
48127	APP20L	+ -	48064	APP21A6-BS12	806593481277	3.1	3.6	1.4	1.63	6	7	24A	370
48128	APP20R	- +	48065	APP21L6-BS12	806593481284	3.1	3.6	1.4	1.63	6	7	24A	370

Case #4

Length: 6.5 in (165mm) • Width: 3.4 in (86mm) • Height: 5.12 in(130)mm

Stock Code	Model No.	Polarity	Replaces	Replaces	UPC	Weight (lb)	Weight w/ box & foam (lb)	Weight (kg)	Weight w/ box & foam (kg)	Case Qty	LFP Actual Ah	Max Charge Current	CCA
48129	APP24L	+ -	48066	APP24A3-BS12	806593481291	4.3	5.4	1.95	2.45	3	10	24A	500
48130	APP24R	- +	48067	APP24L3-BS12	806593481307	4.3	5.4	1.95	2.45	3	10	24A	500
48131	APP30L	+ -	48068 48070	APP27A3-BS12 APP36A3-BS12	806593481314	4.9	5.8	2.22	2.63	3	12	24A	600
48132	APP30R	- +	48069 48071	APP27L3-BS12 APP36L3-BS12	806593481321	4.9	5.8	2.22	2.63	3	12	24A	600